

**HIGHER QUALITY
BETTER SERVICE**

CERTTREE

QUESTION & ANSWER



Provide One Year
Free Update!

<https://www.certtree.com>

Exam : **E20-526**

Title : XtremIO Solutions and
Design Specialist Exam for
Technology Architects

Version : DEMO

- 1.Which Multipathing software is supported by XtremIO?
- A. PowerPatch/VE and NMP on ESXi Host
 - B. MPIO on non-clustered Microsoft Windows Hosts only
 - C. PowerPath/VE on Microsoft Windows VMs hosted by ESXi
 - D. Native MPIO on IBM AIX clusters

Answer: C

2.A customer has a workload with the following attributes:

- . Generates 500.000 IOPs
- . Maximum Bandwidth of 14GB/s

Which XtremIO X2 solution should be recommended to the customer?

- A. 1 X-Brick
- B. 2 X-Brick
- C. 3 X-Brick
- D. 4 X-Brick

Answer: B

3.A customer wants to connect their Storage Controller to Fiber Channel switches using as many Fiber Channel port as possible.

Which port of each storage controller shown in the exhibit should be used?

- A. 1 and 2
- B. 1,2,3 and 4
- C. 2 and 3
- D. 3 and 4

Answer: A

4.You are connecting a Linux host to an XtremIO array. The host will be connected to the array using the Qlogic HBA's.

Based on the recommended best practice, what is the value for the queue depth?

- A. 128
- B. 256
- C. 1024
- D. 8192

Answer: B

5.What should the Oracle Redo Log block size be set to in order to prevent log entries from being misaligned by read-modify-write operators for an Oracle Database?

- A. 4 Kb
- B. 8 Kb
- C. 16 Kb
- D. 24 Kb

Answer: C